

# 600

# COIL-AWAY™ ROLLING SERVICE DOORS



LIGHT-DUTY ROLLING SERVICE DOOR



## THE IDEAL CHOICE WHEN ECONOMY AND FUNCTIONALITY ARE IMPORTANT

- **Unique rolled galvanized steel slat curtain** with bottom weatherseal comes standard
- Fabricated of **24 or 26-gauge galvanized steel**
- Designed to fit **openings up to 16' high and 16' wide**
- Perfect for **light commercial and industrial applications**
- **2-year limited warranty**
- **Options available:**
  - Wind load
  - Chain hoist or motor operation
  - Hood



INDUSTRY LEADING  
COMMERCIAL & INDUSTRIAL SOLUTIONS

# MODEL 600 COIL-AWAY™ LIGHT-DUTY ROLLING SERVICE DOOR

## Standard features at a glance

Maximum standard width	16' (4877 mm)
Maximum standard height	16' (4877 mm)
Curtain	26 ga. galvanized steel up to 12'0" (3658 mm) width; 24 ga. galvanized steel over 14' (4267 mm) height
Slat profile	Flat crown profile type CAW
Finish (interior/exterior)	White/White, White/Brown, Brown/White
Standard mounting	Face of wall
Counterbalance	High tensile helical torsion spring housed in a steel tube or pipe barrel assembly
Brackets	Galvanized steel to support counterbalance and curtain
Operation	Manual push-up up to 100 sq. ft. (9290 sq.mm) or 10' x 10' (3048 mm x 3048 mm) Chain hoist over 100 sq. ft. (9290 sq.mm) or 10' x 10' (3048 mm x 3048 mm)
Standard spring	10,000 cycle
Weatherseals	Bottom
Guides	Cold roll-formed channel and angle
Bottom bar	Extruded aluminum with weatherseal
Lock	Slide bolts on push-up; padlockable chain keeper with chain hoist
Warranty	2-year limited; 3 years/10,000 cycles limited on Overhead Door door and operator system

## Finish options

### Standard colors



Brown



White

## Options

Electric operator or chain hoist
Bottom sensing edge
Hood
Wind load package
Galvanized steel endlocks
Between jambs mounting
PowderGuard® Premium powder coat offers full spectrum of approximately 200 colors as well as color matching to specification

## Slat data

### CAW Slat



Slat	Opening width	Standard	Optional
CAW	Thru 12'4" (3759 mm)	26 ga.	24 ga.
	Thru 16'0" (4877 mm)	24 ga.	

Slats are galvanized and painted.

### Finish details

#### Standard polyester base coat

Two-coat system with polyester based top coat.

#### PowderGuard® Premium powder coat

Polyester powder coat available in approximately 200 RAL colors; custom color match upgrade to architects specs also available. Ideal for wide array of interior and exterior applications to match facility aesthetics.

Actual colors may vary from brochure due to fluctuations in the printing process. Always request a color sample from your Overhead Door Distributor for accurate color matching.



INDUSTRY LEADING  
COMMERCIAL & INDUSTRIAL SOLUTIONS



2501 S. State Hwy. 121 Bus., Suite 200, Lewisville, TX 75067

1-800-929-DOOR • sales@overhaddoor.com

www.overhaddoor.com